

SLG 5100 CARGO BUS CANEVAS SPECIFICATIONS

MOB: +243 818888770,

+243 976047903

e-mail : export@sinotruk-afric.com

MANUFACTURE TIME: 40 DAYS

Model	YC4E160-20/30/42	
Engine	Make: CUMMIS Engine model: CUMMINS L300-20 4 stroke direct injection diesel engine 6 cylinder in-line with water cooling, turbo-charging & intercooling Maximum output: 300hp (118kw) at 2200 rpm according to DIN Cooling system filling quantity (long-term filling): Thermostat with 71 °C opening begin Twin cylinder air compressor Rigid fan	
Clutch	With clutch booster.	
Transmission	Manual, 6 speeds.	
Suspension system	steel leaf spring, F 11 and R 12	
Length	7-8 meters	
Fuel tank:	95 L	
Max. speed(km/h)	95	
Tire	7.50-20	
Luggage compartment(M3)	Without	
Interiors	Integrated environmental conservation interior	
Air conditioner (A/C)	Optional	
Body structure	frame structure	
Standard seats and Number of passengers	2 2+2, 2+4	
Dimensions in mm	Overall Dimension	7990*2450*3350
	Body size	10000
	G.V.W.(kg)	
Standard configuration	Heating system; Heater of fuel water heating; the waste water heatint; Electric folding door; Iron covering on the roof board of cargo compartment. Air conditioner; Enclosed bulkhead or with the bulkhead sliding window;; Access door & lock rod; Height adjustable driver seat; Adjustable passenger seat; Automatic gap adjustable arm; 100 A generator; Reversing radar; Reversing monitor; Model 770 roof hatch; Curtains; 7.50R20 tire;	
Optional configuration	Rear double doors; Deluxe side mirrors; Cabin sliding window; 6 seats for passengers; 3 Dome lamps; Cabin: Vinyl flooring, Fiberboard headliner; Cargo area: Iron diamond plate flooring, Fiberboard headliner, Corrugated iron interior side walls; Bulkhead sliding door; Luggage compartments; 4kg fire extinguisher; Rear bull bar; Model 650 roof hatch;CS-900H/2G defroster.	

The manufacture reserves the right of technical alteration/change for better improvement without prior notice