


## CANEVAS SPECIFICATIONS

MOB: +243 818888770,

+243 976047903

e-mail : export@sinotruk-afric.com

**MANUFACTURE TIME: 40 DAYS**

<b>Model</b>	ZZ5707V3840AJ		
<b>Cabin</b>	HW7D Standard Cab with A/C		
<b>Vehicle Main Dimensions (mm)</b>	L x W x H	8700*3300*4400	
	Wheel base	3850+1500	
<b>Weight in KGS</b>	Tare Weight	23000KG	
	Loading Capacity	75000KG	
	Front axles loading capacity	HF 12 1X12000KG Drum , reinforced axle with double T-cross section, and steering power cylinder assistance	
	Rear axles loading capacity	AC26 2x26000KG Reinforced casted axle housing, differential locks between wheels and axles	
<b>Max. driving speed (km/h)</b>			75
<b>Ratio</b>			10.47
<b>Fuel tank</b>			500L, D shape
<b>Engine</b>	Brand	SINOTRUK	
	Model	D12.42 T2	
	Type	4-stroke direct injection , 6-cylinder in-line with water cooling, turbo-charging and inter-cooling	
	Horse Power (HP)	420HP	
	Emission standard	Euro II	
<b>Gearbox</b>	HW21712, 12 Forwards gear & 2 reverse		
<b>Clutch</b>	Reinforced diaphragm clutch, diameter 430mm		
<b>Steering Gear</b>	ZF8118, power steering, hydraulic steering with power assistance		
<b>Tire</b>	14.00-25 tire with one spare tire		
<b>Brakes</b>	Service brake: dual circuit compressed air brake Parking brake: spring energy, compressed air operating on rear wheels Auxiliary brake: engine exhaust valve brake		

**The manufacture reserves the right of technical alteration/change for better improvement without prior notice**