CANEVAS SPECIFICATIONS

MOB: +243 818888770, +243 976047903 e-mail: export@sinotruk-afric.com

MANUFACTURE TIME: 40 DAYS

Cabin	Driving type 6×4 HOWO Standard cab HOWO 76 Standard cab, with one bed, 70°hydraulically tillable to the front as attached photo for ref.			
Vehicle main Dimensions	Overall dimensions (L×W×H)mm		9800×2600×3950	
	Wheel base (mm)		3600+1350	
	Wheel track (front/rear) (mm)		2041/1850	
	Approach/Departure angle(°)		16/32	
Weight in KGS	Tare Weight		12300	
	Front axles loading capacity		1x9000	
	Rear axles loading capacity		2×16000	
Max. driving speed (km/h)			90	
Engine	Brand		SINOTRUK	
	Model		WD615.57	
	Horse Power (HP)/(KPM)		371HP	
	Emission standard		Euro II	
Gearbox	HW19710, 10 forward & 2 reverse			
Clutch	Reinforced diaphragm clutch, diameter 420mm			
Steering Gear	ZF 8118 power steering, hydraulic steering with power assistance			
Fuel tank (L)	300			
Tire	12.00R20 Radial Tire, 11pcs			
Mixer Body				
Volume	M³	10M³		
Body Thickness	mm	High tensile strength steel 6mm		6mm
Hydraulics	Gear box, Motor, Pump			German or American Brand